### **Passive Loudspeakers**



O

# KINGIE SEFES

The Kinetic Series are passive loudspeakers that offer the legendary performance that Wharfedale Pro has become world famous for. The Kinetic Series offer professional features such as compression drivers, custom designed woofers and PTC HF protection. Speakon/Jack Combination inputs are parallel wired for flexibility and feature throughout the range to ensure compatibility and seamless integration with both professional and beginner equipment.

The Kinetic Series is suitable for a wide range of applications, they are an ideal choice for small bands or portable DJ's that need heavy duty sound reinforcement on a budget.

#### Features

- · Low Distortion, High Power Custom Wharfedale Pro Woofers
- HF Compression Drivers
- 90°x60° Elliptical Waveguides
- High Slope Crossover With High Voltage Components
- PTC HF Driver Protection Circuitry
- Low Resonance Enclosures
- Road-Tough Carpet Finish
- High-Impact Plastic Handles
- High-Impact Plastic Pole Mount Receptacles (Steel On Kinetic 153 & 18B)
- Parallel Speakon/1/4" Jack Inputs
- High Pass Output (Kinetic 18B Only)

#### www.wharfedalepro.com

6

## KINGIG SOFIES



#### **S**pecifications

					No. of Concession, name		Section 1	
	-	and the second		17	STOLEN IN COLUMN			
	and the second se				Sector Sector	and the owner of the owner.	and the	
					1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		3	
	Q							
	Second III	0111					1.1.1.1	
		AS A	0		1.044		Contraction A	
	0	(9)	-		(3)	100	6	
Model	Kinetic 8	Kinetic 12	Kinetic 12M	Kinetic 15	Kinetic 153	Kinetic 215	Kinetic 18B Subwoofer	
Configuration Frequency Response (±3dB)	2-way 70-20kHz	2-way 60-20KHz	2-way monitor 60-20kHz	2-way 50-20KHz	3-way 50-20kHz	Quasi 3-way 45-20kHz	45-250Hz	
Power Handling	70-20KHZ	00-20KH2	00-20682	JU-ZUKHZ	JU-ZUKITZ	43-20KHZ	45-250H2	
Continuous	150W	200W	200W	250W	300W	300W	300W	
Programme	300W	400W	400W	500W	600W	600W	600W	
Peak	600W	800W	800W	1000W	1200W	1200W	1200W	
Nominal Impedance	4Ω	4Ω	4Ω	4Ω	4Ω	4Ω	4Ω	
Sensitivity (1W @ 1m)	96dB	96dB	96dB	97dB	98dB	100dB	98dB	
Max SPL (Calculated)	124dB	125dB	125dB	127dB	129dB	131dB	129dB	
Nominal Horizontal Coverage (@1kHz)	90°	90°	90°	90°	90°	90°		
Nominal Vertical Coverage (@1kHz)	60°	60°	60°	60°	60°	60°		
LF Size	205mm / 8"	305mm / 12"	305mm / 12"	381mm / 15"	381mm / 15"	381mm / 15"	470mm / 18"	
LF Voice Coil	1.53"	2.0"	2.0"	2"	2"	1.5"	2.5"	
LF Driver Number	L01-07010129A	L01-07010130A	L01-07010130A	L01-07010131A	L01-07010131A	ZD-05400-01R	L01-07010028A	
HF Voice Coil	25.4mm / 1"	25.4mm / 1"	25.4mm / 1"	25.4mm / 1"	25.4mm / 1"	25.4mm / 1"		
HF Waveguide Type	Elliptical	Elliptical	Elliptical	Elliptical	Elliptical	Elliptical		
HF Waveguide Exit	30.5mm / 1.2"	30.5mm / 1.2"	30.5mm / 1.2"	30.5mm / 1.2"	30.5mm / 1.2"	30.5mm / 1.2"		
HF Diaphragm Material	Phenolic	Phenolic	Phenolic	Phenolic	Phenolic	Phenolic		
HF Protection	PTC	PTC	PTC	PTC	PTC	PTC		
HF Driver number	ZD-53200-01R	ZD-53200-01R	ZD-53200-01R	ZD-53200-01R	ZD-53200-01R	ZD-53200-01R		
MF Size					165mm / 6.5"			
MF Voice Coil					25.4mm / 1"			
MF Driver Number					ZD-24100-01R			
Enclosure Material and Thickness	12mm / 0.5" particle	12mm / 0.5" particle	12mm / 0.5" particle	12mm / 0.5" particle	12mm / 0.5" particle	12mm / 0.5" particle	15mm / 0.59" particle	
Enclosure Finish	Black Carpet	Black Carpet	Black Carpet	Black Carpet	Black Carpet	Black Carpet	Black Carpet	
Grille Material & Finish	1.0mm Steel	1.2mm Steel	1.2mm Steel	1.2mm Steel	1.2mm Steel	1.2mm Steel	1.2mm Steel	
Pole Mount	35mm / 1 3/8"	35mm / 1 3/8"		35mm / 1 3/8"	35mm / 1 3/8"	35mm / 1 3/8"	35mm / 1 3/8"	
Handles	2 On Sides	2 On Sides	2 On Sides	2 On Sides	2 On Sides	2 On Sides	2 On Sides	
Input Connector Type	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	2x Speakon + ¼" Jack	
HPF Output Connector Type	704 //	12.20 //.	11 5 1/.	17.02 //.	21 5 1/-	25.4.14	1x Speakon + ¼" Jack	
Net Weight	7.84 Kg 17.3 lbs	12.28 Kg 27 lbs	11.5 Kg 25.3 lbs	17.02 Kg 37.4 lbs	21.5 Kg 47.3 lbs	25.4 Kg 55.9 lbs	28.74 Kg	
Groce Waight				37.4 IDS 18.8 Kg	47.3 lbs 23.9 Kg	29.2 Kg	63.2 lbs	
Gross Weight	8.8 Kg 19.4 lbs	13.8 Kg 30.4 lbs	13.7 Kg 30.1 lbs	41.4 lbs	23.9 Kg 52.5 lbs	29.2 Kg 64.2 lbs	31.6 Kg 69.5 lbs	
Dimensions (Unpacked)	13.4 103	50.4 IDS	30.1 103	-1.H IUS	J2.J IUS	UT.2 IUS	03.0 103	
H	429mm / 16.9"	525mm / 20.7"	380(SITU)mm / 14.96"	618mm / 24.3"	725mm / 28.54"	1004mm/39.53"	512mm / 20.16"	
W	272.2/149.6mm / 10.7"/5.9"	362.2/210.1mm / 14.3"/8.27"	366 / 14.4"	437.4/273.5mm / 17.2"/10.77"	473.8/293.7mm / 18.65"/11.56"	437.4/273.5mm/17.22"/10.78"	640mm / 25.19"	
D	253mm / 9.96"	308mm / 12.13"	525mm / 20.7"	330mm / 12.99"	360mm / 14.17"	330mm/12.99"	437mm / 17.2"	
Dimensions (Packed)	,			,		,	,	
H	482mm / 18.97"	586mm / 23.07"	413mm / 16.26"	680mm / 26.77"	786mm / 30.95"	1172mm/46.14"	579mm / 22.79"	
W	299/166mm / 11.8"/6.54"	426/242mm / 16.8"/9.53"	568mm / 22.36"	502/304mm / 19.76"/11.97"	538/324mm / 21.18"/12.76"	538/324mm/21.18"/12.76"	686mm / 27.0"	
D	278mm / 10.9"	348mm / 13.7"	386mm / 15.2"	370mm / 14.57"	400mm / 15.75"	400mm/15.75"	483mm / 19.0"	
Volume	0.031m <sup>3</sup>	0.068m <sup>3</sup>	0.09m <sup>3</sup>	0.1m <sup>3</sup>	0.136m <sup>3</sup>	0.20m <sup>3</sup>	0.192m <sup>3</sup>	

Wharfedale Professional IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU, England www.wharfedalepro.com The information in this brochure is subject to change without notice. All rights reserved ©2011 Wharfedale Pro. Wharfedale Pro is a member of the IAG Group.